

# ARS12PV456



61.75" x 23.38" x 24.38" (H x W x D)

Performance series Pharma-Vac 12 cu.ft. upright all-refrigerator certified to NSF/ANSI 456 Vaccine Storage Standard

**Highlights:**

Certified to NSF/ANSI 456 Vaccine Storage Standard

Intelligent microprocessor digital temperature controller

Improved temperature accuracy with a separate temperature probe for continuous product readout to simulate stored product temperature

**Product Features:**

|                                                    |                                                                                                                                                                                      |
|----------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Certified to NSF/ANSI 456 Vaccine Storage Standard | Designed and tested to comply with the new NSF Vaccine Storage Standard                                                                                                              |
| Purpose-built design                               | Designed and purpose-built for pharmacy, medication, and vaccine applications to support meeting CDC/VFC guidelines                                                                  |
| +/-1°C Variation                                   | The published temperature variation is derived from the maximum deviation of an NTC sensor in a 1 oz. vial located nearest the chamber geometric center during a 24 hour test period |
| Certificate of calibration included                | 2-year calibration certificate included for your records                                                                                                                             |
| Antimicrobial silver ion-coated handle             | Powder-coated handle with naturally occurring silver ions to help reduce the spread of germs                                                                                         |
| Adjustable temperature                             | Intuitive controls let you adjust the interior temperature between +2 to +8°C                                                                                                        |
| Temperature alarm                                  | Visual and audible alarms alert if the interior temperature rises or falls out of set range                                                                                          |
| Remote alarm contacts                              | Electronic controller is equipped with a volt-free contact for alarm forwarding to an external remote system (contacts located in the external rear of the unit)                     |
| Automatic defrost with adjustable cycle defrost    | Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup                                                                                         |

## ARS12PV456 Specifications:

| Overview                   |                     |
|----------------------------|---------------------|
| Height of Cabinet          | 61.75" (157 cm)     |
| Width                      | 23.38" (59 cm)      |
| Width with Door Open       | 23.88" (61 cm)      |
| Depth                      | 24.38" (62 cm)      |
| Depth with Handle          | 26.13" (66 cm)      |
| Depth with door at 90°     | 46.5" (118 cm)      |
| Capacity                   | 12.0 cu.ft. (340 L) |
| Defrost Type               | Automatic           |
| Door                       | White               |
| Cabinet                    | White               |
| US Electrical Safety       | ETL                 |
| Canadian Electrical Safety | ETL-C               |
| Sanitation                 | ETL-S to NSF 456    |
| Amps                       | 1.4                 |
| Voltage/Frequency          | 115 V AC/60 Hz      |
| Weight                     | 184.0 lbs. (83 kg)  |
| Shipping Weight            | 221.5 lbs. (100 kg) |
| Parts & Labor Warranty     | 2 Years             |
| Compressor Warranty        | 5 Years             |
| UPC                        | 761101090665        |
| Refrigerator Features      |                     |
| Door Swing                 | RHD                 |
| Reversible                 | Factory Reversible  |
| Shelf Type                 | Wire                |
| Shelf Qty                  | 7                   |
| Adjustable Shelves         | Yes                 |
| Thermostat Type            | Digital             |
| Fan Type                   | Interior            |
| Refrigerant Type           | R600a               |
| Refrigerant Amount         | 2.11oz.             |
| Interior Light             | Yes                 |
| Temperature Range          | 2 to 8°C            |
| Dimensions                 |                     |
| Interior Height            | 53.0" (135 cm)      |
| Interior Width             | 20.0" (51 cm)       |
| Interior Depth             | 17.0" (43 cm)       |
| Compressor Step Height     | 6.5" (17 cm)        |

|                       |               |
|-----------------------|---------------|
| Compressor Step Width | 20.0" (51 cm) |
| Compressor Step Depth | 5.0" (13 cm)  |

