

Battery Operated Cauteries

High Temp Cauteries

Model	AA01	AA03	AA05	AA09	AA11	AA17	AA21
Tip Configuration	Fine tip	Loop Tip	2" Shaft w/ Loop Tip	5" Shaft Loop Tip	Fine Tip	2" Shaft Fine Tip	Elongated Fine Tip
Temperature (at Activation)	2200° F 1204° C	2200° F 1204° C	2200° F 1204° C	2200° F 1204° C	1500-2100° F 816-1149° C	2200° F 1204° C	1800° F 982° C
Power Supply	3V (2ea - 1.5V AA Batteries)	3V (2ea - 1.5V AA Batteries)	3V (2ea - 1.5V AA Batteries)	3V (2ea - 1.5V AA Batteries)	3V (2ea - 1.5V AA Batteries)	3V (2ea - 1.5V AA Batteries)	3V (2ea - 1.5V AA Batteries)
Shelf Life	4 years	4 years	4 years	4 years	4 years	4 years	4 years

Micro-High Temp Cauteries

Model	AA25	AA27	AA29
Tip Configuration	Fine tip	Loop Tip	Elongated Fine Tip
Temperature (at Activation)	2000° F 1093° C	2000° F 1093° C	1600° F 871° C
Power Supply	3V (2ea - 1.5V AAA Batteries)	3V (2ea - 1.5V AAA Batteries)	3V (2ea - 1.5V AAA Batteries)
Shelf Life	2 years	2 years	2 years

Low-Temperature Cauteries

Model	AA00	AA04	AA02	Micro-Low-Temp AA90
Tip Configuration	Fine tip	Elongated Fine Tip	Fine tip	Fine tip
Temperature (at Activation)	1300° F 704° C	1100° F 593° C	700-1200° F 371-649° C	850° F 545° C
Power Supply	1.5V (1ea - 1.5V AA Batteries)	1.5V (1ea - 1.5V AA Batteries)	1.5V (1ea - 1.5V AA Batteries)	1.5V (1ea - 1.5V AAA Batteries)
Shelf Life	4 years	4 years	4 years	2 years

- | | |
|---|--|
| • Disposable Single Use | • Supplied Individually Packaged Sterile, 10 per box |
| • Constant Burn Time Approx. 10 minutes | • Reusable Styles Available |