



Vibramatic®

Technical Specifications



Built-in timer
and applicator
storage.

Motor -	1/17 horsepower
Output Speed -	20-60 cycles per second
Power Source -	110v or 220v (other voltages available)
Speed Control -	Solid State Electronic
Current Leakage -	under 75 MicroAmps
Power Cord -	10' hospital grade
Drive Cable -	5'
Housing Material -	ABS Cyclac
Configurations -	Caster-stand or table-top mounted
Unit Dimensions -	9 1/2" H x 16 1/2" W x 12 1/2" D
Assembled Dimensions -	44" H x 21" W x 21" D
Unit Weight -	17 Lbs.
Assembled Unit Weight -	26 Lbs.
Shipping Dimensions -	22" x 21" x 20"
Shipping Weight -	37 Lbs. (based on applicator package)
Applicator Packages -	PRO-PKG or RT-PKG recommended
Timer -	Yes
Applicator Storage -	Yes - Built-in top loading bin



GENERAL PHYSIOTHERAPY, INC.

13222 LAKEFRONT DRIVE - EARTH CITY (ST. LOUIS), MISSOURI 63045-1504 - USA
PHONE: (314) 291-1442 TOLL FREE: (800) 237-1832 FAX: (314) 291-1485
www.g5.com

